

Thin wall tubes in fixed-angle rotors must always be used full and with a cap!
Thin wall tubes in swinging bucket rotors must be filled to 3mm of tube top!

OPEN-TOP POLYCLEAR TUBES

Rev. 3

Tube Size	Seton PN Box of 50	Tube Capacity ml	For Beckman Rotor	For Thermo-Sorvall Rotor	For Kontron Rotor	Like Beckman Tube PN	Like Thermo-Sorvall Tube PN
7/16x1-3/8" (11x34mm)	7011	2.2	TLS55	RP55-S	---	347356	45315 45242
7/16x2-3/8" (11x60mm)	7010	4.4	SW60Ti SW56Ti	TH-660	TST60.4 TFT80.4	344062	---
1/2x1-1/4" (13x32mm)	7020	3.0	See Note (4)	---	---	344092	---
1/2x1-5/8" (13x41mm)	7021	4.0	See Note (4)	---	---	344093	---
1/2x2" (13x51mm)	7022	5.0	SW65Ti,SW55Ti SW50.1,SW50, MLS-50	AH-650	TST55.5	344057	---
1/2x2-1/2" (13x64mm)	7023	6.5	50.3Ti,40.3 40.2,50.4Ti(1)	---	TFT45.6	344088	---
9/16x3-1/2" (14x89mm)	7030	12.0	SW41Ti	TH-641	---	344059	6752
9/16x3-3/4" (14x95mm)	7031	12.9	SW40Ti	---	TST41.14	344060	---
5/8x2" (16x51mm)	7043	8.0	SW30.1	---	---	346600	---
5/2x2" (16x52mm)	7048	7.0	---	S50ST	---	---	S309168A
5/8x2-1/2" (16x64mm)	7040	10.2	Ty50	---	---	344089	---
5/8x3" (16x76mm)	7041	12.6	See Note (4)	T-1270,A-1256, T-865.1,T-875	TFT80.13,75, 13.65.13,50.13, 32.13	344085	---
5/8x4" (16x102mm)	7042	17.0	SW32.1 SW28.1Ti SW27.1Ti	AH-629/17 Surespin 630/17	TST28.17	344061	6750
1x2" (25x51mm)	7053	20.0	SW30	AH-629/20	---	346598	---
1x3" (25x76mm)	7050	32.5	SW25.1	---	---	344063	---
1x3-1/2" (25x89mm)	7052	38.5	See Note (5)	AH-629/36 T-1250 Surespin 630/36	TFT70.38,65.38 55.38,50.38 TST28.38	344958	75000471
1-1/2x4" (38x102mm)	7060 (3)	94.0	45Ti,35,21	---	TFT45.94	345777	---

©2000-2016 Seton Scientific

(1) May be used with adapters in the following rotors: Types 90Ti, 80Ti, 75Ti, 70.1Ti, 65, 60Ti, 55.2Ti, 50.2Ti, 50Ti, 45Ti, 42.1, 40, 35 & 21.

(2) May be used with adapters in the following rotors: Types 70Ti, 60Ti, 55.2Ti, 50.2Ti, 45Ti, 42.1, 35, 30 & 21.

(3) PN 7060 is a box of 25 tubes.

(4) Used in the following rotors: 90Ti, 80Ti, 75Ti, 70.1Ti, 65, 50Ti, 50 & 40.

(5) Used in the following rotors: SW32, SW28, SW27, 70Ti, 60Ti, 55.2Ti, 50.2Ti, 42.1 & 30.

(6) Adapter required.

(7) In SW60Ti and TH-660 rotors (11mm dia) use Seton Adapter PN 4109 (Set of 6 adapters);
in SW65Ti, SW55Ti, SW50.1, SW50 rotors (13mm dia) use Seton Adapter PN 4114 (Set of 6).